

Description

tube outside diameter: 5/16", sleeve coupling flareless, corrosion resistant steel, MS21921 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21921J |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4730-00-684-0114 |
| Schedule B: | 7609.00.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21921-5J Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Fabrication Method: | Any Acceptable |
| Nut Style: | Tube Coupling |
| Nut Height: | 0.760 Inches Nominal |
| Width Across Flats: | 0.625 Inches Nominal |
| Length To Shoulder: | 0.562 Inches Nominal |
| Smallest Inside Diameter: | 0.366 Inches Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.500 Inches |
| Nominal Tube Outside Diameter: | 0.312 Inches |
| Seat Angle: | 45.00 Degrees Nominal |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Qq-s-763,class 304 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 96906-ms21921 Government Standard |

How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-5J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.