

Description

Carbon steel, tube outside diameter: 3/8", nut, sleeve coupling, flareless, MS21921 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS219216 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4730-00-810-4499 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21921-6 Specifications

| | |
|---------------------------------------|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Fabrication Method: | Machined |
| Nut Height: | 0.800 Nominal Inches |
| Width Across Flats: | 0.688 Inches Nominal |
| Smallest Inside Diameter: | 0.425 Inches Minimum And 0.430 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.5625 Inches |
| Nominal Tube Outside Diameter: | 0.375 Inches |
| Seat Angle: | 45.00 Degrees Nominal |
| Special Features: | Supports Grumman A10 Aircraft. Thread Series Is Unfj. Nut Style Is A350 Tube Coupling. Length To Shoulder Is "any Acceptable". |
| Material: | 15-5 Ph Steel |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 96906-ms21921 Government Standard |

How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.