

**Description**

Outside diameter: 3/8", corrosion resistant steel, sleeve coupling, flareless, MS21921 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219216J
Minimum Qty (MOQ):	1
NSN:	4730-01-074-6036
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21921-6J Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Any Acceptable
<b>Nut Style:</b>	Tube Coupling
<b>Nut Height:</b>	0.800 Inches Nominal
<b>Width Across Flats:</b>	0.688 Inches Nominal
<b>Length To Shoulder:</b>	0.578 Inches Nominal
<b>Smallest Inside Diameter:</b>	0.425 Inches Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	18
<b>Nominal Thread Size:</b>	0.562 Inches
<b>Nominal Tube Outside Diameter:</b>	0.375 Inches
<b>Seat Angle:</b>	45.0 Degrees Nominal
<b>Material:</b>	Steel Comp 304 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Specification/standard Data:</b>	81343 - As21921 Government Standard

## How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-6j> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.