

Description

Outside diameter: 3/8", corrosion resistant steel, sleeve coupling, flareless, MS21921 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS219216J |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-01-074-6036 |
| Schedule B: | 7318.16.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21921-6J Specifications

| | |
|---------------------------------------|-------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Fabrication Method: | Any Acceptable |
| Nut Style: | Tube Coupling |
| Nut Height: | 0.800 Inches Nominal |
| Width Across Flats: | 0.688 Inches Nominal |
| Length To Shoulder: | 0.578 Inches Nominal |
| Smallest Inside Diameter: | 0.425 Inches Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.562 Inches |
| Nominal Tube Outside Diameter: | 0.375 Inches |
| Seat Angle: | 45.0 Degrees Nominal |
| Material: | Steel Comp 304 Overall |
| Surface Treatment: | Passivate Overall |
| Specification/standard Data: | 81343 - As21921 Government Standard |

How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-6j> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.