

**Description**

tube outside diameter: 1/2", aluminum alloy, sleeve coupling flareless

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS21921-8W](#)

SKU / Model:	MS219218D
Minimum Qty (MOQ):	5
NSN:	4730-01-087-7557
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N MS21921-8D Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Any Acceptable
<b>Nut Style:</b>	Tube Coupling
<b>Nut Height:</b>	0.850 Inches Minimum And 0.870 Inches Maximum
<b>Width Across Flats:</b>	0.871 Inches Minimum And 0.875 Inches Maximum
<b>Length To Shoulder:</b>	0.599 Inches Minimum And 0.619 Inches Maximum
<b>Smallest Inside Diameter:</b>	0.552 Inches Minimum And 0.557 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	16
<b>Nominal Thread Size:</b>	0.750 Inches
<b>Nominal Tube Outside Diameter:</b>	0.500 Inches
<b>Seat Angle:</b>	45.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2014 Overall And Aluminum Alloy 2024 Overall
<b>Specification/standard Data:</b>	96906-ms21921 Government Standard

## How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-8D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.