

P/N MS21921-8D

Military-Fasteners.com

Description

tube outside diameter: 1/2", aluminum alloy, sleeve coupling flareless

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS	219	21-	-8W	

SKU / Model:	MS219218D
Minimum Qty (MOQ):	5
NSN:	4730-01-087-7557
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS21921-8D Specifications

Thread Class:	3b	
Thread Direction:	Right-hand	
Fabrication Method:	Any Acceptable	
Nut Style:	Tube Coupling	
Nut Height:	0.850 Inches Minimum And 0.870 Inches Maximum	
Width Across Flats:	0.871 Inches Minimum And 0.875 Inches Maximum	
Length To Shoulder:	0.599 Inches Minimum And 0.619 Inches Maximum	
Smallest Inside Diameter:	0.552 Inches Minimum And 0.557 Inches Maximum	
Thread Series:	Unjf	
Thread Quantity Per Inch:	16	
Nominal Thread Size:	0.750 Inches	
Nominal Tube Outside Diameter:	0.500 Inches	
Seat Angle:	45.0 Degrees Nominal	
Material:	Aluminum Alloy 2014 Overall And Aluminum Alloy 2024 Overall	
Specification/standard Data:	96906-ms21921 Government Standard	

How to Order

Order this tube coupling nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-8D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.