

Description

tube outside diameter: 1/2", aluminum alloy, sleeve coupling flareless

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21921-8W](#)

SKU / Model:	MS219218D
Minimum Qty (MOQ):	5
NSN:	4730-01-087-7557
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS21921-8D Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Fabrication Method:	Any Acceptable
Nut Style:	Tube Coupling
Nut Height:	0.850 Inches Minimum And 0.870 Inches Maximum
Width Across Flats:	0.871 Inches Minimum And 0.875 Inches Maximum
Length To Shoulder:	0.599 Inches Minimum And 0.619 Inches Maximum
Smallest Inside Diameter:	0.552 Inches Minimum And 0.557 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.750 Inches
Nominal Tube Outside Diameter:	0.500 Inches
Seat Angle:	45.0 Degrees Nominal
Material:	Aluminum Alloy 2014 Overall And Aluminum Alloy 2024 Overall
Specification/standard Data:	96906-ms21921 Government Standard

How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-8D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.