

## Description

corrosion resistant steel 304, tube outside diameter: 1/2", sleeve coupling flareless, MS21921 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS219218J
Minimum Qty (MOQ):	2
NSN:	4730-00-859-3517
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21921-8J Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Any Acceptable
<b>Nut Style:</b>	Tube Coupling
<b>Nut Height:</b>	0.860 Inches Nominal
<b>End Item Identification:</b>	Rtf33-p-3/5/9 (c/ec-135, B-52h) Aircraft Engine. Tf33-pw-102 (c-135e, Ec-135h/k/p), Sh-60f Asw Carrier Based Helicopter. Mh-53e Helicopter. Tf-33-p-7 (c-141 A/b) Aircraft Engine. Lamps Mk Iii Landing System Helicopter.
<b>Width Across Flats:</b>	0.875 Inches Nominal
<b>Length To Shoulder:</b>	0.609 Inches Nominal
<b>Smallest Inside Diameter:</b>	0.552 Inches Nominal
<b>Thread Series:</b>	Unj
<b>Thread Quantity Per Inch:</b>	16
<b>Nominal Thread Size:</b>	0.750 Inches
<b>Nominal Tube Outside Diameter:</b>	0.500 Inches
<b>Seat Angle:</b>	45.00 Degrees Nominal
<b>Criticality Code Justification:</b>	Feat
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Steel Comp 304 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Specification/standard Data:</b>	96906-ms21921 Government Standard

## How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921-8j> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.