

P/N MS21921V10P

Military-Fasteners.com

Description

tube outside 5/8", sleeve coupling flareless, corrosion resistant steel, cadmium plated

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

Alternate Part Numbers

| MS21921-10 | |
|-------------------------|---|
| SKU / Model: | MS21921V10P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-01-543-0008 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21921V10P Specifications

| Thread Class: | 3b |
|---|--|
| Thread Direction: | Right-hand |
| Fabrication Method: | Any Acceptable |
| Nut Style: | Tube Coupling |
| Nut Height: | 0.970 Inches Minimum And 0.990 Inches Maximum |
| Width Across Flats: | 1.000 Inches Nominal |
| Length To Shoulder: | 0.677 Inches Minimum And 0.697 Inches Maximum |
| Smallest Inside Diameter: | 0.690 Inches Minimum And 0.695 Inches Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 14 |
| Nominal Thread Size: | 0.875 Inches |
| Nominal Tube Outside Diameter: | 0.625 Inches |
| Seat Angle: | 45.00 Degrees Nominal |
| Part Name Assigned By Controlling Agency: | Nut, Sleeve Coupling, Flareless |
| Special Features: | Corrosion Resistant Steel (15-5) With Cadmium Plating |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 81343 - As21921 Professional/industrial Association Standard |

How to Order

Order this tube coupling nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921V10P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.