

Description

tube outside 5/8", sleeve coupling flareless, corrosion resistant steel, cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21921-10](#)

SKU / Model:	MS21921V10P
Minimum Qty (MOQ):	1
NSN:	4730-01-543-0008
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21921V10P Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Fabrication Method:	Any Acceptable
Nut Style:	Tube Coupling
Nut Height:	0.970 Inches Minimum And 0.990 Inches Maximum
Width Across Flats:	1.000 Inches Nominal
Length To Shoulder:	0.677 Inches Minimum And 0.697 Inches Maximum
Smallest Inside Diameter:	0.690 Inches Minimum And 0.695 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	14
Nominal Thread Size:	0.875 Inches
Nominal Tube Outside Diameter:	0.625 Inches
Seat Angle:	45.00 Degrees Nominal
Part Name Assigned By Controlling Agency:	Nut, Sleeve Coupling, Flareless
Special Features:	Corrosion Resistant Steel (15-5) With Cadmium Plating
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Specification/standard Data:	81343 - As21921 Professional/Industrial Association Standard

How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921V10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.