

## Description

tube outside 1/2", nut, sleeve coupling flareless, corrosion resistant steel, cadmium plated, MS21921 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

#### [MS21921-8](#)

SKU / Model:	MS21921V8P
Minimum Qty (MOQ):	1
NSN:	4730-01-543-0367
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



\* See page 2 for technical characteristics

## P/N MS21921V8P Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Fabrication Method:</b>	Any Acceptable
<b>Nut Style:</b>	Tube Coupling
<b>Nut Height:</b>	0.850 Inches Minimum And 0.870 Inches Maximum
<b>Width Across Flats:</b>	0.875 Inches Nominal
<b>Length To Shoulder:</b>	0.599 Inches Minimum And 0.619 Inches Maximum
<b>Smallest Inside Diameter:</b>	0.552 Inches Minimum And 0.557 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	16
<b>Nominal Thread Size:</b>	0.750 Inches
<b>Nominal Tube Outside Diameter:</b>	0.500 Inches
<b>Seat Angle:</b>	45.00 Degrees Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Nut, Sleeve Coupling, Flareless
<b>Special Features:</b>	Corrosion Resistant Steel (15-5) With Cadmium Plating
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	81343 - As21921 Professional/Industrial Association Standard

## How to Order

Order this tube coupling nut from our inventory online by visiting <https://military-fasteners.com/nuts/tube+coupling+nuts/MS21921V8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.