

Description


Outer diameter: 5/8", corrosion resisting steel, flareless, MS21922 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2192210C
Minimum Qty (MOQ):	5
NSN:	4730-00-752-9581
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21922-10C Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.800 Inches Nominal
Flange Width:	0.090 Inches Nominal
Flange Outside Diameter:	0.750 Inches Nominal
Seat Angle In Deg:	12.000
Sleeve Outside Diameter:	0.707 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.625 Inches Nominal
Material:	Steel, Corrosion Resisting
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Flareless
Surface Treatment:	Passivated

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-10C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.