

Description

outer diameter: 3/4", corrosion resistant steel, MS21922 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2192212C
Minimum Qty (MOQ):	1
NSN:	4730-00-752-9626
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21922-12C Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.750 Inches Nominal
Flange Width:	0.090 Inches Nominal
Flange Outside Diameter:	0.938 Inches Nominal
Seat Angle In Deg:	35.000
Sleeve Outside Diameter:	0.836 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.750 Inches Nominal
Material:	Steel,corrosion Resisting,per Std Below
Material:	Steel,corrosion Resisting,per Std Below
Surface Treatment:	Passivate
Style Designator:	Flareless
Surface Treatment:	Passivated

How to Order

Order this tube fitting clinch sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-12C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.