

Description

tube outside 1/8", sleeve coupling, flareless, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS219222 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-01-189-4793 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE
AVAILABLE

P/N MS21922-2 Specifications

| | |
|---|---|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.410 Inches Nominal |
| Flange Width: | 0.062 Inches Minimum And 1.000 Inches Maximum |
| Flange Outside Diameter: | 0.203 Inches Nominal |
| Seat Angle In Deg: | 12.0 |
| Sleeve Outside Diameter: | 0.165 Inches Minimum And 0.175 Inches Maximum |
| Hose/tube Outside Diameter For Which Designed: | 0.125 Inches Nominal |
| Material: | Steel Or Steel, Fed Std 66, Comp 12I14 |
| Material: | Steel Or Steel, Fed Std 66, Comp 12I14 |
| Surface Treatment: | Cadmium |
| Style Designator: | Flareless |
| Surface Treatment: | Cadmium |

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.