

Description

tube outside 1/8", sleeve coupling, flareless, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS219222
Minimum Qty (MOQ):	2
NSN:	4730-01-189-4793
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

P/N MS21922-2 Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.410 Inches Nominal
Flange Width:	0.062 Inches Minimum And 1.000 Inches Maximum
Flange Outside Diameter:	0.203 Inches Nominal
Seat Angle In Deg:	12.0
Sleeve Outside Diameter:	0.165 Inches Minimum And 0.175 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	0.125 Inches Nominal
Material:	Steel Or Steel, Fed Std 66, Comp 12I14
Material:	Steel Or Steel, Fed Std 66, Comp 12I14
Surface Treatment:	Cadmium
Style Designator:	Flareless
Surface Treatment:	Cadmium

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.