

## Description

tube outside 1/8", sleeve coupling, flareless, carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS219222
Minimum Qty (MOQ):	2
NSN:	4730-01-189-4793
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N MS21922-2 Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.410 Inches Nominal
<b>Flange Width:</b>	0.062 Inches Minimum And 1.000 Inches Maximum
<b>Flange Outside Diameter:</b>	0.203 Inches Nominal
<b>Seat Angle In Deg:</b>	12.0
<b>Sleeve Outside Diameter:</b>	0.165 Inches Minimum And 0.175 Inches Maximum
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.125 Inches Nominal
<b>Material:</b>	Steel Or Steel, Fed Std 66, Comp 12I14
<b>Material:</b>	Steel Or Steel, Fed Std 66, Comp 12I14
<b>Surface Treatment:</b>	Cadmium
<b>Style Designator:</b>	Flareless
<b>Surface Treatment:</b>	Cadmium

## How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.