

P/N MS21922-3

Description

Tube outside diameter: 3/16", carbon steel, flareless

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS219223

Minimum Qty (MOQ): 5

NSN: 4730-00-289-8618

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti









^{*} See page 2 for technical characteristics

P/N MS21922-3 Specifications

| Casehardening Indicator: | Not Casehardened |
|--|---|
| Overall Length: | 0.440 Inches Minimum And 0.460 Inches Maximum |
| Flange Width: | 0.060 Inches Minimum And 0.065 Inches Maximum |
| Flange Outside Diameter: | 0.312 Inches Nominal |
| Seat Angle In Deg: | 37.0 |
| Sleeve Outside Diameter: | 0.252 Inches Minimum And 0.256 Inches Maximum |
| Hose/tube Outside Diameter For Which Designed: | 0.188 Inches Nominal |
| Material: | Steel, Mil-s-13433, Type 1-canceled |
| Material: | Steel, Mil-s-13433, Type 1-canceled |
| Surface Treatment: | Cadmium |
| Style Designator: | Flareless |
| Surface Treatment: | Cadmium |

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-3 and selecting the selecting the selecting the selecting the selecting the selecting that the selecting the selecting that the sele