

Description

corrosion resistant steel - tube outside 3/16", sleeve coupling flareless

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS219223C |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-729-7035 |
| National Motor Freight: | 052250, Pipe R Tubing R Pipe Fittings Noi |

NO IMAGE
AVAILABLE

P/N MS21922-3C Specifications

| | |
|---|----------------------|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.450 Inches Nominal |
| Flange Width: | 0.060 Inches Nominal |
| Flange Outside Diameter: | 0.312 Inches Nominal |
| Seat Angle In Deg: | 12.0 |
| Sleeve Outside Diameter: | 0.252 Inches Nominal |
| Hose/tube Outside Diameter For Which Designed: | 0.188 Inches Nominal |
| Material: | Steel, Ams 5643 |
| Material: | Steel Comp 630 |
| Surface Treatment: | Passivate |
| Style Designator: | Flareless |
| Surface Treatment: | Passivated |

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.