

**Description**

tube outside diameter: 1/4", sleeve coupling, flareless, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219224C
Minimum Qty (MOQ):	2
NSN:	4730-00-720-0461
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21922-4C Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.520 Inches Nominal
<b>End Item Identification:</b>	Supports Grumman A10a Aircraft
<b>Flange Width:</b>	0.060 Inches Nominal
<b>Flange Outside Diameter:</b>	0.359 Inches Nominal
<b>Seat Angle In Deg:</b>	35.0
<b>Sleeve Outside Diameter:</b>	0.309 Inches Nominal
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.250 Inches Nominal
<b>Material:</b>	Steel, Ams 5643
<b>Material:</b>	Steel Comp 630
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Flareless
<b>Surface Treatment:</b>	Passivated, Mil-s-5002

## How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-4C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.