

Description

tube outside diameter: 1/4", sleeve coupling, flareless, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS219224C
Minimum Qty (MOQ):	2
NSN:	4730-00-720-0461
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21922-4C Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.520 Inches Nominal
End Item Identification:	Supports Grumman A10a Aircraft
Flange Width:	0.060 Inches Nominal
Flange Outside Diameter:	0.359 Inches Nominal
Seat Angle In Deg:	35.0
Sleeve Outside Diameter:	0.309 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.250 Inches Nominal
Material:	Steel, Ams 5643
Material:	Steel Comp 630
Surface Treatment:	Passivate
Style Designator:	Flareless
Surface Treatment:	Passivated, Mil-s-5002

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-4C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.