

Description

tube outside diameter: 5/16", sleeve coupling flareless, carbon steel, MS21922 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS219225
Minimum Qty (MOQ):	5
NSN:	4730-00-289-8620
Schedule B:	7326.90.8588
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS21922-5 Specifications

Casehardening Indicator:	Casehardened
Overall Length:	0.590 Inches Nominal
Flange Width:	0.060 Inches Nominal
Flange Outside Diameter:	0.422 Inches Nominal
Seat Angle In Deg:	35.0
Sleeve Outside Diameter:	0.373 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.313 Inches Nominal
Material:	Steel, Qq-s-637, Comp 1213
Material:	Steel Comp 1213
Surface Treatment:	Cadmium And Chromate
Style Designator:	Flareless
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 2

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.