

Description

tube outside diameter: 3/8", sleeve coupling flareless, Carbon steel, MS21922 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS219226 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-554-7398 |
| Schedule B: | 7307.92.3030 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N MS21922-6 Specifications

| | |
|---|-------------------------------------|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.660 Inches Nominal |
| End Item Identification: | Grumman Aerospace Corp A10 Aircraft |
| Flange Width: | 0.060 Inches Nominal |
| Flange Outside Diameter: | 0.484 Inches Nominal |
| Seat Angle In Deg: | 12.0 |
| Sleeve Outside Diameter: | 0.435 Inches Nominal |
| Hose/tube Outside Diameter For Which Designed: | 0.375 Inches Nominal |
| Material: | Steel, Mil-s-13433-canceled |
| Material: | Steel Comp 12114 |
| Surface Treatment: | Cadmium |
| Style Designator: | Flareless |
| Surface Treatment: | Cadmium |

How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.