

**Description**

Tube outside diameter: 3/6", corrosion resistant steel, sleeve coupling, flareless, MS21922 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219226C
Minimum Qty (MOQ):	1
NSN:	4730-00-618-7621
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21922-6C Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.660 Inches Nominal
<b>Flange Width:</b>	0.060 Inches Nominal
<b>Flange Outside Diameter:</b>	0.484 Inches Nominal
<b>Seat Angle In Deg:</b>	35.0
<b>Sleeve Outside Diameter:</b>	0.435 Inches Nominal
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.375 Inches Nominal
<b>Material:</b>	Steel, Ams 5643
<b>Material:</b>	Steel Comp 630
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Flareless
<b>Surface Treatment:</b>	Passivated, Mil-s-5002

## How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-6C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.