

**Description**

tube outside diameter: 1/2", coupling, flareless, carbon steel, MS21922 series sleeve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS219228
Minimum Qty (MOQ):	2
NSN:	4730-00-289-8618
Schedule B:	7307.92.3030
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21922-8 Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.440 Inches Minimum And 0.460 Inches Maximum
<b>Flange Width:</b>	0.060 Inches Minimum And 0.065 Inches Maximum
<b>Flange Outside Diameter:</b>	0.312 Inches Nominal
<b>Seat Angle In Deg:</b>	37.0
<b>Sleeve Outside Diameter:</b>	0.252 Inches Minimum And 0.256 Inches Maximum
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.188 Inches Nominal
<b>Material:</b>	Steel, Mil-s-13433, Type 1-canceled
<b>Material:</b>	Steel, Mil-s-13433, Type 1-canceled
<b>Surface Treatment:</b>	Cadmium
<b>Style Designator:</b>	Flareless
<b>Surface Treatment:</b>	Cadmium

## How to Order

Order this clinch tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/clinch+tube+fitting+sleeves/MS21922-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.