

Description

outside diameter: 3/8", union, bulkhead and universal, flareless tube, aluminum alloy, MS21924 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21924D6
Minimum Qty (MOQ):	1
NSN:	4730-00-541-1749
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21924D6 Specifications

Thread Class:	3a Center Bulkhead
Thread Class:	3a All Ends
End Item Identification:	Grumman A10 Aircraft; 10n Aircraft; Tomcat F-14a
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flareless (tube) 1st End
Connection Type:	Threaded External Boss 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches Center Bulkhead
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Nominal Overall Length:	1.797 Inches
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf Center Bulkhead
Specification/standard Data:	96906-ms21924 Government Standard

How to Order

Order this straight tube to boss adapter from our inventory online by visiting <https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/MS21924D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.