

Description

MS21924 series fitting

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21924J4
Minimum Qty (MOQ):	2
NSN:	4730-00-720-1588
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21924J4 Specifications

Thread Class:	3a Center Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	135.0 Deg Celsius Single Response
Connection Style:	External Seat For Gasket Seal (boss) 2nd End
Connection Style:	Flareless (tube) 1st End
Connection Type:	Threaded External Boss 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches All Ends
Nominal Thread Size:	0.438 Inches Center Bulkhead
Seat Angle:	12.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 1st End
Nominal Overall Length:	1.656 Inches
Special Features:	Supports Grumman A10 Aircraft
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Aeronautical Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf Center Bulkhead
Specification/standard Data:	96906-ms21924 Government Standard

How to Order

Order this straight tube to boss adapter from our inventory online by visiting <https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/MS21924J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.