

Description

MS24392J4 Tube Nipple

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AN815-4J](#)

SKU / Model:	MS24392J4
Minimum Qty (MOQ):	5
NSN:	4730-00-684-6912
Schedule B:	AN81.54.J
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24392J4 Specifications

Thread Class:	3a All Ends
Connection Style:	Flared (tube) All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches All Ends
Seat Angle:	37.000 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.250 Inches All Ends
Nominal Overall Length:	1.250 Inches
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Style Designator:	Flared W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms24392 Government Standard And 81349-mil-f-5509 Government Specification

How to Order

Order this tube nipple from our inventory online by visiting <https://military-fasteners.com/fittings/tube+nipples/MS24392J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.