

**Description**

Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | MS2452326                            |
| Minimum Qty (MOQ):      | 1 EA                                 |
| NSN:                    | 5930-00-683-1632                     |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



\* See page 2 for technical characteristics

# P/N MS24523-26 Specifications

|   |   |
|---|---|
| Unable To Decode:                                     | Unable To Decode  |
| Body Style:   | Bushing Mount   |
| Bushing Length:                                       | 0.455 Inches Minimum And 0.485 Inches Maximum   |
| Body Length:  | 1.270 Inches Maximum  |
| Body Width:   | 0.635 Inches Maximum  |
| Body Height:  | 0.890 Inches Minimum And 0.930 Inches Maximum   |
| Actuator Style:                                       | Round   |
| Actuator Diameter:                                    | 0.237 Inches Minimum And 0.243 Inches Maximum   |
| Actuator Height:                                      | 0.665 Inches Minimum And 0.695 Inches Maximum   |
| Actuator Position-action Relationship:                | Up Position Maintained And Down Position Maintained   |
| Maximum Voltage Rating In Volts:                      | 115.0 Ac And 28.0 Dc  |
| End Item Identification:                              | Strategic Wepon Systems   |
| Inclosure Type:                                       | Fully Inclosed  |
| Mounting Method:                                      | Threaded Bushing  |
| Features Provided:                                    | Actuator Seal   |
| Thread Quantity Per Inch:                             | 32  |
| Nominal Thread Size:                                  | 0.469 Inches  |
| Nonpile-up Contact Arrangement:                       | 1 Pole, Single Throw, Both Positions Maintained Single Switch Unit  |
| Contact Load Current Rating At Maximum Rated Voltage: | 15.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 4.000 Amperes Lamp Dc And 15.000 Amperes Resistive Ac And 7.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac  |
| Test Data Document:                                   | 81349-mil-s-3950 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |
| Thread Series Designator:                             | Uns   |
| Terminal Type And Quantity:                           | 2 Screw   |

## How to Order

Order this switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS24523-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.