

Description

2 position, 2 pole, standard lever, screw terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2452430
Minimum Qty (MOQ):	1
NSN:	5930-00-588-8305
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



P/N MS24524-30 Specifications

Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Weatherproof
Bushing Length:	0.450 Inches Minimum And 0.490 Inches Maximum
Body Length:	1.340 Inches Maximum
Body Width:	0.910 Inches Maximum
Body Height:	0.990 Inches Minimum And 1.030 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.235 Inches Minimum And 0.245 Inches Maximum
Actuator Height:	0.660 Inches Minimum And 0.720 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Momentary
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Single Throw, Normally Open, Momentary Action Single Switch Unit
Criticality Code Justification:	Feat
Contact Load Current Rating At Maximum Rated Voltage:	18.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 5.000 Amperes Lamp Dc And 11.000 Amperes Resistive Ac And 8.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
Special Features:	Item Must Comply With Rqmt Of The Desc Production Standard No. L01705
Thread Series Designator:	Uns
Terminal Type And Quantity:	4 Screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/electrical/toggle+switches/MS24524-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.