

Description

MS24547-1 Sensitive Switch

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS245471
Minimum Qty (MOQ):	2
NSN:	5930-00-477-6494
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24547-1 Specifications

Body Style:	Hole Mounted
Hazardous Locations/environmental Protection:	Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.186 Inches Minimum And 0.190 Inches Maximum
Body Length:	0.510 Inches Maximum
Body Width:	0.210 Inches Maximum
Body Height:	0.350 Inches Nominal
Unthreaded Mounting Hole Diameter:	0.087 Inches Minimum And 0.090 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.057 Inches Minimum And 0.067 Inches Maximum
Actuator Height:	0.050 Inches Maximum
Actuator Free Position Height:	0.355 Inches Maximum
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Nonpile-up Contact Arrangement:	1 Pole, Double Throw, One Position Momentary Single Switch Unit
Switch Release Force:	1.0 Ounces Minimum
Criticality Code Justification:	Feat
Switch Actuating Force:	5.0 Ounces Maximum
Actuator Movement:	0.020 Pretravel Inches Maximum And 0.004 Overtravel Inches Minimum And 0.005 Differential Inches Maximum
Contact Load Current Rating At Maximum Rated Voltage:	7.000 Amperes Resistive Dc And 4.000 Amperes Inductive Dc And 2.500 Amperes Lamp Dc And 7.000 Amperes Resistive Ac And 7.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
Special Features:	Item Must Comply With Requirements Of Desc Production Std No. L00767
Terminal Type And Quantity:	3 Turret

How to Order

Order this sensitive switch from our inventory online by visiting <https://military-fasteners.com/switches/sensitive+switch/MS24547-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.