

## P/N MS24586C170

## **Description**

MS24586 series spring

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS24586-C170

SKU / Model: MS24586C170

Minimum Qty (MOQ): 10

NSN: 5360-00-825-3413

ECCN: EAR99

National Motor Freight: 177940, Springs:springs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24586C170 Specifications

Inside Diameter:	0.418 Inches Nominal
End Style:	Short Twisted Hook Both Ends
Spring Free Length:	2.332 Inches Nominal
Coil Quantity:	33-1/2
Design Type:	Closed
Load Rating:	4.830 Pounds Nominal
Coil Helix Direction:	Right-hand Or Left-hand
Spring Deflection Rate:	1.090 Pounds Per Inch Nominal
Spring Free Outside Diameter:	0.500 Inches Nominal
Hook Radius:	0.209 Inches Nominal Both Ends
Spring Length Under Load:	6.300 Inches Nominal
Coil To Hook Inside Length:	0.418 Inches Nominal Both Ends
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Qq-w-423,form 1,cond B Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Style Designator:	Cylindrical

## **How to Order**

Order this spring from our inventory online by visiting <a href="https://military-fasteners.com/springs/misc+springs/MS24586C170">https://military-fasteners.com/springs/misc+springs/MS24586C170</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.