

Description

Fastener Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2461540 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-483-0550 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24615-40 Specifications

| | |
|--|---|
| Fastener Length: | 0.969 Inches Minimum And 1.031 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.340 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.190 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24615-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.