

Description

Fastener Length: 1/4", MS24617 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS51861-12](#)

SKU / Model:	MS246171
Minimum Qty (MOQ):	100
NSN:	5305-00-879-3825
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24617-1 Specifications

Fastener Length:	0.219 Inches Minimum And 0.281 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Submarine Auxillary And Miscellaneous Systems; Missile, Minuteman Lgm-30; Chaparral/vulcan Ads/ssamd; Aircraft, Orion P-3; Shop Equipment, Contact Maintenance, Truck Mounted; Airborne Mobile Dir Air Spt Ctl (2id), (02m Jul83) (an/uyq-3a); Trident Hull Structure; Support Equipment, B-1 Aircraft; Aircraft, Stratolifter C-135; Mixier Rotary Tiller
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1022 Overall Or Steel Comp 1030 Overall Or Steel Comp 1524 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24617-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.