

Description

Fastener Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246172
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-883-0632
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24617-2 Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall Or Steel Comp 1030 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2,class 3 Fed Spec All Treatment Responses Overall

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24617-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.