

P/N MS24621-1

Description

Fastener Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS246211
Minimum Qty (MOQ): 25

25

NSN: 5305-00-053-1108

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24621-1 Specifications

Fastener Length:	0.094 Inches Minimum And 0.125 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:aircraft, Airlifter C-17a; Aircraft (ac-130h, Mc-130h, Ec-130h, Hc-130); Helicopter, Advance Attack, Ah-1w; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Aircraft, C-2a (reprocured); Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Sas (starting Air Sys), Ffg-7; Helicopter, Mh-53e; Engine, Aircraft, Tf-33-p-7 (c-141a/b)
Features Provided:	Casehardened
Nonmachine Thread Style:	Dog Type (type B Or C)
Nonmachine Nominal Thread Diameter:	0.086 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24621-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.