

Description

Fastener Length: 63/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2462134 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-432-7954 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24621-34 Specifications

| | |
|---|--|
| Fastener Length: | 0.969 Inches Minimum And 1.031 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Nonmachine Nominal Thread Diameter: | 0.164 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24621-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.