

**Description**

Fastener Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS246221
Minimum Qty (MOQ):	145 EA
NSN:	5305-00-058-2096
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS24622-1 Specifications

<b>Fastener Length:</b>	0.094 Inches Minimum And 0.125 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.155 Inches Minimum And 0.167 Inches Maximum
<b>Head Height:</b>	0.053 Inches Minimum And 0.062 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s:helicopter, Search And Rescue, Hh-60h; Helicopter, Uscg Search And Rescue, Hh-60j; Engine, Aircraft T-700; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Mh-53e; Helicopter, Advance Attack, Ah-1w; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Jet Aircraft Start Unit; Consolidated Targets; Engine, Aircraft, Tf39-ge-1 (c-5a)
<b>Nonmachine Thread Style:</b>	Dog Type (type B Or C)
<b>Nonmachine Nominal Thread Diameter:</b>	0.086 Inches
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 420 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24622-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.