

P/N MS24622-11

Description

Length: 17/32", MS24622 series screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS2462211

Minimum Qty (MOQ): 20

NSN: 5305-00-147-3224

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24622-11 Specifications

Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Intermediate Forward Test Equip (ifte) System; Wasp Class Lhd; Supply Class Aoe; Trainer, B-1b Aircraft; Nimitz Class Cvn; Radar Set, Lightweight 3d (an/tps-59); Forrestal Class Cv; Ground Mobile Force Satellite Comm Term (an/tsc-93a); Support Equipment, B-1 Aircraft; Spruance Class Dd (963)
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24622-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24622-11 and selecting the quantity you