

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2462555
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-133-3854
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE  
AVAILABLE

## P/N MS24625-55 Specifications

<b>Fastener Length:</b>	0.344 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.473 Inches Minimum And 0.492 Inches Maximum
<b>Head Height:</b>	0.162 Inches Minimum And 0.175 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Features Provided:</b>	Casehardened
<b>Nonmachine Thread Style:</b>	Wide Flute (type H Or Bt) Or Thd Flute (type Bf)
<b>Nonmachine Nominal Thread Diameter:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	Bf Type Or Bt Type

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24625-55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.