

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2462810
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-052-8888
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24628-10 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.195 Inches Minimum And 0.225 Inches Maximum
Head Height:	0.038 Inches Minimum And 0.047 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Thru Slot (type D) Or Double Flute (type F) Or Thru Slot (type 6) Or Wide Flute (type T)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24628-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.