

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS2462810 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-052-8888 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS24628-10 Specifications

| | |
|--|--|
| Fastener Length: | 0.250 Inches Nominal |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.195 Inches Minimum And 0.225 Inches Maximum |
| Head Height: | 0.038 Inches Minimum And 0.047 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nonmachine Thread Style: | Thru Slot (type D) Or Double Flute (type F) Or Thru Slot (type 6) Or Wide Flute (type T) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.112 Inches |
| Material: | Steel Comp 410 Overall Or Steel Comp 420 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24628-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.