

Description

Fastener Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS246291 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-855-8006 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N MS24629-1 Specifications

| | |
|---|--|
| Fastener Length: | 0.094 Inches Minimum And 0.125 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.155 Inches Minimum And 0.167 Inches Maximum |
| Head Height: | 0.053 Inches Minimum And 0.062 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Thru Slot (type D) Or Double Flute (type F) Or Thru Slot (type 6) Or Wide Flute (type T) |
| Nonmachine Nominal Thread Diameter: | 0.086 Inches |
| Material: | Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall |
| Material Document And Classification: | Aisi Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24629-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.