

**Description**

Fastener Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS246292
Minimum Qty (MOQ):	10
NSN:	5305-00-052-6907
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS24629-2 Specifications

<b>Fastener Length:</b>	0.156 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.155 Inches Minimum And 0.167 Inches Maximum
<b>Head Height:</b>	0.053 Inches Minimum And 0.062 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Features Provided:</b>	Casehardened
<b>Nonmachine Thread Style:</b>	Thru Slot (type D) Or Double Flute (type F) Or Thru Slot (type 6) Or Wide Flute (type T)
<b>Nonmachine Nominal Thread Diameter:</b>	0.086 Inches
<b>Material:</b>	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24629-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.