

## P/N MS24629-2

### **Description**

Fastener Length: 3/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS246292

Minimum Qty (MOQ): 10

NSN: 5305-00-052-6907

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS24629-2 Specifications

Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Thru Slot (type D) Or Double Flute (type F) Or Thru Slot (type 6) Or Wide Flute (type T)
Nonmachine Nominal Thread Diameter:	0.086 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1524 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall

# **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24629-2">https://military-fasteners.com/screws/machine+screws/MS24629-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.