


Description

Fastener Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS246302
Minimum Qty (MOQ):	100
NSN:	5305-00-959-1086
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24630-2 Specifications

Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Thru Slot (type D) Or Double Flute (type F) Or Wide Flute (type T) Or Thru Slot (type 6)
Nonmachine Nominal Thread Diameter:	0.086 Inches
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24630-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.