

P/N MS24630-66

Description

Fastener Length: 1/2", MS24630 series screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS2463066

Minimum Qty (MOQ): 50

NSN: 5305-01-109-0587

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24630-66 Specifications

Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Thru Slot (type D) Or Double Flute (type F) Or Wide Flute (type T) Or Thru Slot (type 6)
Nonmachine Nominal Thread Diameter:	0.190 Inches
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	D Type Or F Type Or G Type Or T Type

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24630-66 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24630-66 and selecting the quantity you