

P/N MS24630-67

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2463067

Minimum Qty (MOQ): 20 EA

NSN: 5305-00-323-2834

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24630-67 Specifications

Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Nominal Thread Diameter:	0.190 Inches
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	D Type Or F Type Or G Type Or T Type

How to Order

Order this tap/thread cut screw from our inventory online by visiting https://military-fasteners.com/screws/tapping+screws/MS24630-67 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.