

Description

MS24658-22D Toggle Switch

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2465822D
Minimum Qty (MOQ):	1
NSN:	5930-00-843-8990
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



* See page 2 for technical characteristics

P/N MS24658-22D Specifications

Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Vaportight
Bushing Length:	0.450 Inches Minimum And 0.490 Inches Maximum
Body Length:	1.270 Inches Maximum
Body Width:	0.635 Inches Maximum
Body Height:	0.910 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.400 Inches Minimum And 0.440 Inches Maximum
Actuator Height:	1.030 Inches Minimum And 1.070 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Maintained And Center Position Maintained
Actuator Position-locking Relationship:	Center Position Locked Out
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
End Item Identification:	Mrap - Common Nsn - Used On Rg33 Cat I And 59 Other Weapon Systems
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	1 Pole, Double Throw, Three Positions Maintained Single Switch Unit
Contact Load Current Rating At Maximum Rated Voltage:	20.000 Amperes Resistive Dc And 15.000 Amperes Inductive Dc And 5.000 Amperes Lamp Dc And 15.000 Amperes Resistive Ac And 10.000 Amperes Inductive Ac And 3.000 Amperes Lamp Ac
Thread Series Designator:	Uns
Terminal Type And Quantity:	3 Screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/electrical/toggle+switches/MS24658-22D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.