

Description

length: 1/2", diameter: 5/64", corrosion resistant steel, MS24665 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24665227
Minimum Qty (MOQ):	100
NSN:	5315-00-855-6804
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron



P/N MS24665-227 Specifications

Diameter:	0.072 Inches Minimum And 0.076 Inches Maximum
Underloop Length:	0.438 Inches Minimum And 0.625 Inches Maximum
Point Type:	Hammer Lock Or Extended Prong Square Cut
Hardness Rating:	60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-227> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.