

Description

diameter: 5/64", length: 3/4", corrosion resistant steel , MS24665 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS24665229 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5315-00-239-8023 |
| ECCN: | EAR99 |
| National Motor Freight: | 094380, Cotter Pins / Spring Cotters Iron |



P/N MS24665-229 Specifications

| | |
|---|---|
| Diameter: | 0.072 Inches Minimum And 0.076 Inches Maximum |
| Underloop Length: | 0.688 Inches Minimum And 0.875 Inches Maximum |
| Point Type: | Extended Prong Square Cut |
| Hardness Rating: | 60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall |
| Material Document And Classification: | Astm A493 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Astm A380 Assn Std Single Treatment Response Overall |
| Style Designator: | Standard |

How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-229> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.